

SAFETY DATA SHEET
EFIVE HEAVY DUTY DEGREASER

Page 1
Issued: 17/09/2002
Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: EFIVE HEAVY DUTY DEGREASER

Use / description of product: Irritant.

Company name: The Supplies House Ltd
Unit 21
Interchange East Business Park
Grosvenor Way
London
E5 9ND
Tel: 0208 8068666
Fax: 0208 8068686

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: DISODIUM METASILICATE 1-10%
EINECS: 229-912-9 CAS: 6834-92-0
[C] R34; [Xi] R37

- 2-(2-BUTOXYETHOXY)ETHANOL 1-10%
EINECS: 203-961-6 CAS: 112-34-5
[Xi] R36
- 2-BUTOXYETHANOL 1-10%
EINECS: 203-905-0 CAS: 111-76-2
[Xn] R20/21/22; [Xi] R36/38
- 01824700 1-10%
CAS: 68439-45-2
[Xn] R22; [Xi] R41
- 02845000 1-10%
CAS: 1300-72-7
[Xi] R36

3. HAZARDS IDENTIFICATION

Main hazards: Irritating to eyes and skin.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

[cont...]

SAFETY DATA SHEET
EFIVE HEAVY DUTY DEGREASER

4. FIRST AID MEASURES (ACTION)

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.
- Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.
- Ingestion:** Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.
- Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

5. FIRE-FIGHTING MEASURES

- Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.
- Exposure hazards:** Corrosive. In combustion emits toxic fumes.
- Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions:** Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.
- Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.
- Clean-up procedures:** Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

- Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.
- Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed.
- Suitable packaging:** Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- Hazardous ingredients:** 2-(2-BUTOXYETHOXY)ETHANOL
WEL (8 hr exposure limit): 100 mg/m³ WEL (15 min exposure limit): 100 mg/m³

SAFETY DATA SHEET

EFIVE HEAVY DUTY DEGREASER

- 2-BUTOXYETHANOL
WEL (8 hr exposure limit): 25 ppm WEL (15 min exposure limit): 50 ppm

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Colourless

Odour: Characteristic odour

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Soluble

Also soluble in: Most organic solvents.

Viscosity: Non-viscous

Flash point°C: 70

pH: >12.5

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

- Hazardous ingredients:** DISODIUM METASILICATE
ORL MUS LD50 770 mg/kg
ORL RAT LD50 1153 mg/kg
- 2-(2-BUTOXYETHOXY)ETHANOL
ORL MUS LD50 6050 mg/kg
ORL RAT LD50 4500 mg/kg
 - 2-BUTOXYETHANOL
IVN RAT LD50 307 mg/kg
ORL MUS LD50 1230 mg/kg
ORL RAT LD50 470 mg/kg
 - 01824700
ORL RAT LD50 >200<2000 mg/kg
 - 02845000
ORL RAT LD50 >7000 mg/kg

SAFETY DATA SHEET
EFIVE HEAVY DUTY DEGREASER

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Hazardous ingredients: 01824700
FISH 96H LC50 1-10 mg/l

Mobility: Readily absorbed into soil.

Persistence and degradability: Biodegradable.

Bioaccumulative potential: No bioaccumulation potential.

Other adverse effects: Negligible ecotoxicity.

13. DISPOSAL CONSIDERATIONS

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 1760 **ADR Class:** 8

Packing group: III **Classification code:** C9

Shipping name: CORROSIVE LIQUID, N.O.S. (DISODIUM METASILICATE)

Labelling: 8 **Hazard ID no:** 80

**IMDG / IMO**

UN no: 1760 **Class:** 8

Packing group: III **EmS:** 8-15

Marine pollutant: . **Labelling:** 8

IATA / ICAO

UN no: 1760 **Class:** 8

Packing group: III **Packing instructions:** 818(P&CA); 820(PAO)

Labelling: 8

15. REGULATORY INFORMATION

Hazard symbols: Irritant.



Risk phrases: R36/38: Irritating to eyes and skin.

SAFETY DATA SHEET
EFIVE HEAVY DUTY DEGREASER

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.2: R34: Causes burns.
R37: Irritating to respiratory system.
R36: Irritating to eyes.
R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.
R36/38: Irritating to eyes and skin.
R22: Harmful if swallowed.
R41: Risk of serious damage to eyes.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.